

# LUXURY SKIM COAT

FOR INTERIOR & EXTERIOR WITH SIKAMEN 162 CTM



**LUXURY SKIM COAT** is the composite made from Portland cement, naturally active ingredient, calcium, and another additive particularly, with the addition of **SIKAMEN 162 CTM** super-elastic polymer, **LUXURY SKIM COAT** is strengthened greatly in adhesive, anti-alkalization and damp-proof for complete plan layer. This product is recommended by experts in the world and manufactured in the latest technology line imported from **The Federal Republic of Germany**. It is easy for use with little force required with lard amount of paint, so it is helpful to save more coast but applied a wider area. This product was inspected quality at building material center and quality measurement and standard department.

## Main ingredients:

- Concrete adherence after 96h:  $\geq 0.2$  mpa TCVN 6017: 1995
- Compression strength after 96h: 20 - 25 mpa TCVN 6017: 1995
- Volume stability not greater than 11cm TCVN 3121: 1995
- Time for concretion
  - + Begin, approximately: 240 minutes
  - + End, approximately: 345 minutes
- Fineness, not greater than (after-sieved remainder 0.08mm): 3.2 TCVB 4030: 1985
- Surface hardness after 96 hours not less than 0.05 TCVN 2098: 1993

## Feature:

Color: White-covering: 1.2 m<sup>2</sup>/kg for 2 coats depend on the surface

## Usage:

1. Pour 10kg **LUXURY SKIM COAT** soluble with 3.5 – 4 liters of clean water.
2. Stir well to make mastic soluble perfectly in the water.
3. To make the smooth surface, apply 1 to 2 layers in an interval from 20 – 30 minutes.
4. After completion, leave it dried in 4 to 5 hours before scrubbing the surface with an emery paper.
5. After scrubbing, clean with a damp cloth before apply paint to the surface.
6. Apply base coating or paint to the surface after 24 hours.

**Tool: Metal trowel or plastic palette knife.**

## Surface preparation

All surfaces must be clean and dried, dust-free, with no oil, wax, or any other impurities, and the moisture must not be over 15%. The big gape in the wall surface or ceiling must be filled before applying.

## Storage:

- Store in a dried, cool place any kept away from reach of children.
- 12 months in a closed bag, do not heap over 10 bags, avoid dragging on the floor.

## Note:

Do not apply with thickness over 3mm. Do not apply on painted wall or smoothed floor surface.